

Effective Preliminary Hazard Analysis for Battery Energy Storage Systems

Denis Barritt
Risk Engineer, R4Risk
RISK 2025
23 May 2025


R4Risk

L14, 222 Kings Way
(PO Box 5023)
SOUTH MELBOURNE VIC 3205

P: (03) 9268 9700
E: solutions@r4risk.com.au
www.r4risk.com.au

- In 10 years installed capacity of battery energy storage systems (BESS) has grown from 0 to 2 GW
- Next 10 years the Market Operator forecasts installed capacity to further grow to ~12 GW
- Development in areas not historically used for industry

Grid-scale BESS power capacity (MW)



Source: AEMO Generation Information, Modo Energy

Notes: Commercially operational scheduled battery energy storage projects in the NEM. Data accurate as of **MODOENERGY** 18/11/2024.


- Thermal runaway reaction
 - Fire, explosion
- Firefighting challenges
 - Self-oxidizing material
 - Stranded energy
 - Toxic smoke / run-off
 - Explosion hazard
- Toxic smoke can impact nearby land uses



Fire at Moss Landing BESS (Liza Azil)

- Rate of failure incidents has dropped significantly
 - Standards/regulations being developed
- BESS fires/explosion have limited potential to cause far-field fatality
 - **No reported off-site fatalities**

Global Grid-Scale Storage Deployment and Failure Statistics



- Failures are very visible and make compelling news
- Failures have resulted in first responder injury & fatality
- New technology, new risks

A Net-Zero Chernobyl: California Battery Fire Releases Tons of Carcinogenic Metals and Toxic Gases 2

Toxic materials blanket communities, farms, and a sensitive estuary

FEB 20 • TUCO'S CHILD AND GENE NELSON, PH.D.




UPDATE: Moss Landing Battery Storage Facility Reignites a Month after First Fire

Officials advise residents to close doors, windows

FEB 20 • TUCO'S CHILD



- Preliminary Hazard Analysis is conducted at development application
- Identifies potential land use conflicts and demonstrates that they can be managed
- Opportunity to implement additional risk controls before final design / construction




- 500 MW / 2GWh BESS
- Located in rural Queensland
- Zoned as rural land use
- Council requested preliminary hazard analysis considering the criteria described in State Code 21



Image: AdobeStock

- Queensland State Code 21 describes 11 land use planning performance outcomes for hazardous chemical facilities
 - Five relate to off-site impact/risk
 - Four relate to DG storage & handling
 - Two relate to facility siting and design
- Compliance with the code is demonstrated by compliance with performance outcomes or demonstration of risk reduced ‘so far as is reasonably practicable’
- Application is normally triggered by quantities of scheduled materials as per Major Hazard Facility regulation

- Preliminary Hazard Analysis had dual focus:
 - Demonstrate lack of land use conflict per State Code 21 criteria
 - Demonstrate that on-site and off-site people risk is acceptable
- Risk assessment was qualitative
 - 5x5 risk matrix



- Hazard Identification
 - Review of literature / industry history, local natural hazards
- Hazards Identified
 - Natural Hazards
 - Electrical hazards
 - Power station hazards
 - Battery hazards
- Examples:
 - Moisture ingress, high ambient temperature, control system failure, manufacturing defects

- Consequence Assessment
 - Assigned on-site / off-site consequence severity
 - Based on severity, identified potential for MI (i.e. fatality or permanent disability)
- Results
 - Several events with potential for Major Incident on-site
 - Driven by impact of transformer explosion and electrocution
 - NO events with potential for Major Incident off-site
 - BESS fire not potential to result in off-site fatality

- Identified design preventative / mitigative controls
 - **Standard Preventative:** Battery cooling systems, battery management system with thermal runaway protection, high-level BESS management system
 - **Standard Mitigative:** Smoke / fire detection, sprinkler system, hydrogen gas detection and ventilation, fire-rated BESS walls
- Identified standard site controls which should be implemented as part of the Safety Management System
 - **Standard Preventative:** Preventative maintenance program, safe work practices, equipment design standards, site security, emergency preparedness plans, etc.
 - **Standard Mitigative:** Emergency response plan, pre-incident plans, emergency stops, etc.

- Risk Assessment
 - Determine 'risk rating' based on likelihood and severity
 - Found that risks were controlled very well by vendor design and typical Safety Management System
- State Code 21 Compliance
 - Assessment of compliance against 11 Performance Outcomes
 - Demonstrated that off-site impact was not credible

- Demonstrated compliance with State Code 21
- Provided local council / community overview of risk profile
- Provided operator with independent review of design safety
- Identified hazards / potential risk controls early in project lifecycle

